


THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO YAMETER AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

1		2		3		4		5		6		7		8		9		10		Customer drawing	
REV	ECN NO		DESCRIPTION					DATE		APPROVED		<div>RoHS</div>									
A	-		NEW RELEASED					2022.01.05		MAY.YU											







Electrical specifications:
Use of voltage range: 30V
Current range: 0.5A
Temperature range: -20°C~+80°C

Material specifications
Connector: DisplayPort Standard
Body Shell: Black ABS

Electrical testing of finished cable
100% Open / Short / Miswiring testing
Insulation resistance: DC150V 10MΩMin
Conductor resistance: 3Ω Max



UNMARKED TOLERANCES		TITLE STANDARD DISPLAYPORT SOCKET/SOCKET ADAPTER		<div> Yameter</div> <div></div>			
DIMENSIONS	TOLERANCE						
x.	±0.5						
x.x	±0.25						
x.xx	±0.15						
0 to 500	+15 / -0	CUSTOMER	-	CUSTOMER PART NO.	-	 	
> 501	+3%/-0 of length	DRAWN BY	MAY.YU	PART NUMBER	DP-ASAS-ADAPTER	SIZE	REV
ANGLES		CHECKED BY	BILL.LEE	DRAWING NUMBER	DP-ASAS-ADAPTER	A4	A
x°	±1°	APPROVED BY	TIGER.WANG	SCALE FREE	ALL DIMENSION UNIT IN MM	SHEET 1 OF 1	

0 10 20 30 40 50 60 70 80 90 100 110 120