



THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO YAMETER AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

	1	2	3	4	5	6	7	8	9	10	Customer drawing
REV	ECN NO	DESCRIPTION			DATE	APPROVED					
A	-	NEW RELEASED			2020.07.28	MAY.YU					

RoHS




Material:

1. Insulation: PA, Black
2. Contact: Copper Alloy, Gold-Plated
3. M8 Metal Thread: Copper Alloy, Nickel-Plated
4. Shell: Copper Alloy, Nickel-Plated
5. O-Ring: NBR, Black
6. Connect Contact: Copper Alloy, Gold-Plated
7. Screw: Stainless iron
8. Cable Seal: Silicon, Black
9. Cable Clamp: PA, Black
10. Pressing Nut: Copper Alloy, Nickel-Plated

Technical Data:

1. Standard: IEC61076-2-104
2. Rated Voltage: 60V DC
3. Rated Current: 4A
4. Rated Temperature: $-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$
5. Durability: ≥ 100 Times Cycles
6. Protection Degree: IP67 (Correct locking state)
7. Applicable Cable Diameter: $\phi 3 \sim 5\text{mm}$



Connector Table 1

Yameter Part No.	Coding & Pins	Plug Pin out	Contact Size(mm)	Rated Current	Rated Voltage
M08AM03A6BK01	A Code 3 Pin		1.0	4A	60V/DC
M08AM04A6BK01	A Code 4 Pin		1.0	4A	60V/DC

UNMARKED TOLERANCES		TITLE M8 CONNECTOR PLUG METAL FIELD INSTALLATION STRAIGHT WITH SHIELD		 Yameter 					
DIMENSIONS	TOLERANCE								
x.	±0.5								
x.x	±0.25								
x.xx	±0.15								
0 to 500	+15 / -0	CUSTOMER	-	CUSTOMER PART NO.	-				
> 501	+3%/-0 of length	DRAWN BY	MAY.YU	PART NUMBER	M08AMXXA6BK01		SIZE	REV	
ANGLES		CHECKED BY	BILL.LEE	DRAWING NUMBER	M08AMXXA6BK01		A4	A	
x°	±1°	APPROVED BY	TIGER.WANG	SCALE FREE	ALL DIMENSION UNIT IN MM			SHEET 1 OF 1	

Yameter



0 10 20 30 40 50 60 70 80 90 100 110 120