| | | 1 | | 2 | 3 | | 4 | 5 | Customer drawings | \$ |
|---|-----|---|--|--------|--------------|----------|-----|----------------------|-------------------|----|
| | REV | ECN NO | DESCRIPTION | | DATE | APPROVED | | | | |
| | AA | - | NEW RELEAS | SED | 2020.07.28 | CLARA | 1 | | | |
| A | | | | | ł | | ~56 | | | A |
| В | | | | | φ20 M12x1 | | | | | В |
| c | | Contact Metal SI Snap Rinds Snap Rinds Insulation Insulation Clamp R O-Ring: Cable C Sealing | : Copper nrapnel: S ng: Stainl nell: Zinc n Housing: ing: Copp NBR, Bla amp: PA, Gasket: | Black. | | | | SUPPER DE CONTRACTOR | | c |

11. Pressing Nut: Zinc Alloy, Plated Nickel.

Technical Data:

1

www.bomcan.com

- 1. Standard: IEC61076-2-109
- 2. Rated Voltage: 60V DC
- 3. Rated Current: 0.5A
- 4. Rated Temperature: -40°C~+85°C
- 5. Durability: ≥ 100 Times Cycles
- 6. Protection Degree: IP67 (Correct locking state)

2

3

| BOMCAN | J |
|--------|---|
|--------|---|

This drawing contains information that is proprietary to BOMCAN and should not be used without written permission. Powered by bomcan.com

| DESCRIPTION | M12 X CODE ETHERNET CONNECTOR METAL STRAIGHT SOCKET ASSEMBLY | | | | | | | | |
|-------------|--|---|-----------|--------------|------|-------|------|------------------------|--|
| DWG NO | M12X08SM01ST | | BOMCAN PA | M12X08SM01ST | | | D | | |
| DRAWN BY | CLARA 2020.07.28 | | CUSTOMER | - | | | | | |
| CHECKED BY | CALEB 2020.07.28 | ; | SIZE: A4 | SHEET | UNIT | S | CALE | Third angle projection | |
| APPROVED BY | BILL 2020.07.28 | | REV: AA | 1 of 1 | MN | I F | REE | $\bigcirc - [-]$ | |
| 4 | | | 5 | | | A4 | | | |