


1	2	3	4	5
REV	ECN NO	DESCRIPTION	DATE	APPROVED
AA	-	NEW RELEASED	2017.03.15	CLARA




**Electrical specifications:**  
 Use of voltage range: 5V  
 Current range: 2A  
 Temperature range: -20°C~+80°C

**Material specifications**  
 Cable: USB4 Cable  
 Connector: USB4 Connector  
 Shell Boot: Aluminum alloy

**Mechanical properties**  
 Minimum bending radius: Fixed installation: 8x Cable OD  
 Flexible installation: 10x Cable OD

**Electrical testing of finished cable**  
 100% Open / Short / Miswiring testing  
 Insulation resistance: DC300V 10MΩ  
 Conductor resistance: 5Ω

**Manufacturer: Bomcan**



This drawing contains information that is proprietary to BOMCAN and should not be used without written permission. Powered by bomcan.com

DESCRIPTION	USB4 CABLE ASSEMBLY			
DWG NO	-	BOMCAN PART No	USB4 CABLE	
DRAWN BY	CLARA 2017-03-15	CUSTOMER P/N	-	
CHECKED BY	CALEB 2017-03-15	SIZE: A4	SHEET	UNIT
APPROVED BY	BILL 2017-03-15	REV: AA	1 of 1	MM
			SCALE	Third angle projection
			FREE	

www.bomcan.com